

Pilot Test and Bench-scale Studies of Arsenic Removal by Adsorptive Media



Malcolm Siegel, PhD, MPH

Sandia National Laboratories Albuquerque, NM

March 19, 2008
2008 New Mexico Rural Water Association
Conference





Outline of Talk

- Background why we have a new Arsenic MCL.
- Arsenic Water Technology Partnership
 - Screening of technologies for pilot studies
 - Sandia Labs Pilot Test program
- Frontiers of Science
 - Understanding media performance
 - Rapid testing techniques
- What this all means in the real world-
 - Helping communities deal with the new Standard
 - Sandia arsenic website
 - NM Small Business Assistance Program



Sandia Labs Arsenic Team Members

- Malynda Aragon lead field engineer
- Alicia Aragon RSSCT studies
- Melody Nocon, Hongting Zhao lab studies
- Randy Everett, William Holub Jr., Brian Dwyer,
- Jerome Wright, Justin Marbury, Emily Wright, Michelle Shedd, Carolyn Kirby, Paul McConnell, Linnah Neidel, Nik Rael, Andres Sanchez, David Stromberg, Zac Satterfield
- Prof. Shuguang Deng, New Mexico State



'The King of Poison and the Poison of Kings'

Mass poisoning by arsenic - the premier global public health problem?

- Skin Cancer, Skin lesions
- Bladder Cancer
- Lung Cancer
- Cardiovascular Disease
- Blackfoot Disease

These are result of exposure to relatively high doses over extended period of time.

Other effects of concern include diabetes, cancers of liver and kidney, birth defects, developmental problems





Background for 2006 MCL for Arsenic

- 2006 Reduction of drinking water Maximum Concentration Level (MCL) for arsenic from 50 ppb to 10 ppb was intended to reduce incidence of bladder cancer and other cancers in US.
- Southwestern United States is characterized by high and variable background levels for arsenic
- Estimated national annual costs of implementing 10 ppb
 MCL range from \$165M to \$605M to save 7 33 lives.
 - \$5M \$23.9M /life saved
 - \$1.3M \$6.6M/ year of life saved
 - About 1 life/500,000 exposed persons per year
- New MCL is controversial due to high costs and uncertain health benefits.



Populations Studies are Ambiguous

Studies prior to 2001 Standard

- Some studies carried out in populations in Taiwan, South America show elevated bladder cancer risks. ("relative risk" = 5 −11).
- As concentrations were generally above 50 μ g/L.
- Results of studies of US and European populations at lower As concentrations show no increased risk or are ambiguous.

Post-2001 studies

- Results: do not suggest that chronic exposures to arsenic at low levels (50 100 μ g/L) lead to increased mortality risk for bladder or lung cancer for the majority of populations studied.
- Some studies suggest interaction between smoking and exposure to arsenic <u>may</u> lead to increased risk for bladder and lung cancers;
 - Smokers may experience a higher risk at levels below 100 μ g/L
- Elevated bladder cancer *incidence* in New Mexico at >10 μ g/L suggested recently
- Potential role of arsenic in endrocrine disruption, developmental disorders

Unintended Consequences of new MCL for Arsenic

- The health effects from income redistribution may have adverse health consequences.
 - \$90/month additional cost for rural NM household
- Injury risks from water treatment may exceed the benefits.
 - Based on traffic accident statistics and distance from chemical supply sources for treatment
 - Results depend on assumed dose-response model and treatment technology
- Rural water utilities may cease to operate.
- Rural residents may switch from a public supply to a unregulated private well.



Key Questions

- Is my system or private well likely to have elevated levels of arsenic?
- What are the best methods to remove arsenic to comply with new MCL?
- How can I figure out the answer the question #2?





Is a high level of arsenic likely?

What controls distribution and behavior of arsenic in the environment?




Volcanic Sources of Arsenic


- Strongly enriched in volcanic gases compared to magma
 - enrichment factor = 1000 1000000
- Abundant in silicic volcanics
 - derived volcaniclastic sediments
 - associated hydrothermal systems
 - As is a pathfinder elements in prospecting for hydrothermal gold deposits



Increase of Arsenic in Natural Waters


- Reductive dissolution of iron oxides
 - co-release of adsorbed and structural As
- Reductive desorption of As(V)
 - strongly sorbed As(V) -> weakly sorbed As(III)
- Competitive desorption
 - phosphate, bicarbonate, silicate, dissolved organics
- pH changes
 - increased pH leads to As(V) desorption








pH, Speciation, and Sorption





High Arsenic in New Mexico's Waters



What is the best method to remove arsenic?

Is there a magic bullet?




Can advances in water treatment technology significantly reduce costs?

Arsenic Water Technology Partnership

- Congressional Appropriation \$13M FY03 FY06
- DOE- funded peer-reviewed, cost-shared research program to develop and demonstrate innovative technologies for removal and disposal of arsenic from drinking water
- Partner Roles
 - Bench-Scale Studies (AwwaRF)
 - Demonstration Studies (Sandia)
 - Economic Analysis/Outreach (WERC)
- Focus on small systems
 - 40% of resources directed to rural and Native American utility needs
 - Minimize costs capital, operating, maintenance
 - Minimize residual quantities & disposal costs



AWTP Technology Screening Process



- Innovation
- Performance
- Cost
- Complexity
- Maturity

Sources of new technologies

- Vendors
- Universities
- Government labs

Suggested Pilot Technologies



AWTP Technology Screening Programs

Sandia Arsenic Treatment Vendors Forum

- Open session allows Vendors to present product descriptions
- Closed session review by Technical Evaluation Teams

Awwa Research Foundation

- Technical Review Committee defines research objectives
- Grants are awarded through competitive, peer-reviewed RFP process

WERC Design Contest

 WERC utilizes its existing Design Contest in order to obtain innovative arsenic removal technologies.



Sandia Vendor Forum Description

- Held at New Mexico Environmental Health Conferences in Albuquerque, 2003-2005.
- Format
 - Public presentations by vendors.
 - Vendors privately interviewed by Technology Evaluation Teams
 - Four five-person teams of water treatment experts at each Forum.
 - Each vendor interviewed by at least two teams.
- Twenty-seven different vendors evaluated at the three Forums.
 - Nine vendors in 2003, twelve in 2004, ten in 2005.
 - Four of the 27 vendors attended two Forums.
 - Two universities were among the 27 vendors.



Top Five Ranked Vendors at Forums

2003	2004	2005
Hydroglobe – TiO ₂	Purolite – Hybrid resin	Purolite Hybrid resin
MEI - ZrO ₂	BASF- GFO	ResinTech
Kinetico C/F	Filtronics C/F	EaglePicher – La-coated DE
AdEdge – GFO (Severn Trent)	DOW – TiO ₂	ADA – Coated silicate
Filtronics C/F	ResinTech – Hybrid resin	Virotec – mixed oxides from Bauxite

Report is available.



Innovations -industry and academia

- •Fe, Ti, Cu, Zr or mixed metal oxides in granules formed by chemical precipitation or nanoparticle agglomeration. (e.g. AdEdge, Kemiron, Argonide, Graver)
- Coating granular activated carbon (GAC), strong base anion exchangers resin or polymeric ligand exchangers with nanoparticulate metal oxides. (e.g. Purolite, Resintech, Auburn University, Arizona State)
- Coating inexpensive natural media or waste products with metal oxides or other functional groups. (e.g. ADA, Virotec, Lawrence Berkeley Labs)
- Increased surface area and chemical selectivity based on fibrous or gel substrates coated by metal oxides or materials with sulfhydryl functional groups. (e.g. NMSU, Weber State, Drexel University)




Sandia Pilot Test Concepts

- Side-by-side demonstrations of technologies tested by AwwaRF bench-scale program, WERC design contest, University programs, or commercial technologies vetted through Vendor Forums
 - Test duration: 3 9 months; longer, if multiple pilots at same site
 - Test size: 0.3 2 gpm
 - Different technology classes: adsorptive media, Coagulation/Filtration, membranes
 - Cooperative effort between Sandia, Technology Owner and Site Owner
- Test Protocols developed with help from NSF International, academia, industry during 2004-2005



Test Sites in New Mexico





New Mexico Pilot Sites – Water Quality

Site	Total As/As(III)	V (ppb)	SO ₄ (ppm)	Fe (ppm)	рН
Socorro	42 ppb / 0 ppb	11	29	0.4	8.0
Anthony	20 ppb / 18 ppb	2	180	0.15	7.7
Rio Rancho	19 ppb / < 1 ppb	15	100	<0.10	7.7
Jemez Pueblo	20 ppb / 19 ppb	<1	24	1.2	7.5

Site	Cond. (μS/cm)	TOC (ppm)	Ca Hard (ppm CaCO ₃)	Alkalinity (ppm CaCO ₃)	SiO ₂ (ppm)
Socorro	360	0.5	44	120	25
Anthony	1380	0.8	66	180	37
Rio Rancho	630	ND	62.5	184	22
Jemez Pueblo	770	2.0	155	290	50



First Community Pilot: Socorro, NM


- 100% groundwater source for drinking water
- 2 warm springs (90°F) provide
 500 gpm, 35 55 ppb As(V)
 by gravity flow.
- Formerly site of tap for bottled water company;
- Optimal F for oral health
- Phase 1: Feb-Oct 2005
 - Tested
 - Fe oxides: ED33, ARM200
 - Resin AsXnp
 - Ti-oxide Metsorb
 - Zr-oxide Isolux
 - EBCT study of E33
 - 2,4,5 min










SEM Photos of Adsorptive Media








Different ways to describe performance



Calculation of Column Arsenic Loading Capacity







Media Performance in Socorro, NM

Arsenic Removal Capacity

Parameter	*ARM200 FeOx	Metsorb - TiOx	*AsX ^{np}	Isolux ZrOx	E33 (FeOx)
BV to 10 ppb	8,600	13,000	27,000	32,000	43,000
Capacity at 10 ppb, mg/g	0.60	0.70	1.38	1.67	3.56
BV at C/Co = 0.8	33,000	87,000	53,000	63,000	>63,000
Capacity at C/Co = 0.8	1.15	2.26	2.10	2.23	> 4.62



^{*}AsX^{np} batch was defective, ARM200 was preproduction batch

Media Performance in Socorro, NM Phase 2b (Ambient pH vs. pH 6.8)

Phase 2b:

- Side-by side comparisons of 5 media at 2 pH levels (ambient and pH 6.8)
 - ArsenX^{np} New, QC'd batches
 - Isolux larger cartridge
 - Kemiron FeOx media—CFH-12
 - SANS Sandia proprietary media
 - Metsorb TiOx media
- Evaluate inadvertent effects of treatment
 - Loss of pH control
 - Loss of flow
- Evaluate AwwaRF & University media (pH 6.8)
 - AwwaRF: Auburn University (Poly-lig-IX), ASU (Fe-GAC)
 - University Media: NMSU (Solgel), NMT (coated-volcanic)




Media Performance in Socorro, NM

Phase 2b (Ambient pH vs. pH 6.8)

Phase 2b:


• pH Adjustment using CO₂ gas







Media Performance in Socorro, NM Phase 2 (pH = 6.8 vs. 8)



Better performance at lower pH.

Media

Second Community Pilot: Anthony, NM

- 100% groundwater source for drinking water
- Warm springs (~85°F) provide 240-270 gpm, 20 ppb As - mainly As(III).
- High sulfates, TDS
- Intermittent Flow Operation
- 4 Phases included 13 different sorbent media







Second Community Pilot: Anthony, NM (Desert Sands MDWCA)


- Phase 1: August 2005
 - FeOx: E33, ARM200, CFH12
 - ZrOx: Isolux
 - TiOx: Metsorb, Adsorbsia
 - SANS: mixed oxides
 - Resins: ASM-10HP, ArsenX^{np}
 - La, Fe, Mg-coated diatomaceous earth: NXT-2
- Phase 2: December 2005
 - FeOx-Coated GAC
 - Fe-coated silicate
 - Also: re-loaded ArsenX^{np} column

- Phase 3: June 2006
 - La, Fe, Mg-coated
 diatomaceous earth: NXT-2
 - Modified zeolite: Redisorb
 - New batch ARM200




Best Results of Desert Sands Study

(final phases not completed)



Results from Studies of "Experimental" Media



Outline of Talk

- Background why we have a new As MCL.
- Arsenic Water Technology Partnership
 - Screening of technologies for pilot studies
 - Sandia Labs Pilot Test program
- Frontiers of Science
 - Understanding media performance
 - Rapid testing techniques
- What this all means in the real world-
 - Helping communities deal with the new Standard
 - Sandia arsenic website
 - NM Small Business Assistance program



Research Program - Overall Objective



Full scale treatment


Develop rapid testing methods and models to reduce time and costs required to determine the most effective adsorptive treatment technology for small systems.



Pilot scale 6-12 months




RSSCT & isotherm Days-weeks



Models: days- hrs



Performance of Adsorptive Media




Controlling factors

Sorption equilibria
Intraparticle diffusion rates
Uniform flow




pH, Speciation, and Sorption




Chemical models help estimate relative performance.



Batch Isotherm Results (Socorro, NM)




Sorption isn't the whole story: Shape of mass transfer zone determines capacity





Predicting Diffusion and Transport: Rapid Small Scale Column Tests




Proportional Diffusivity design




- Reduce media sizes and column diameter
- Use higher hydraulic loading rate and shorter EBCT
- Dimensional analysis and similitude
- Tests take days (CD) to weeks (PD)



Socorro I Pilot and RSSCT Breakthrough Curves for E33 (4 min. EBCT)



Pilot and RSSCT Breakthrough Curves for Metsorb Media



Estimates of Arsenic Sorption Capacity from Different Tests (Socorro Phase I)


	E33 (FeOOH)	ARM200 (FeOOH)	Metsorb (TiO ₂)
BV to 10ppb (pilot)	43,000	8,600	13,000
As at 10ppb (pilot)	3.56 mg/g	0.6 mg/g	0.7 mg/g
BV to 10ppb (RSSCT)	43,000 (PD)	6000 (CD)	12,800 (PD)
As at 10 ppb (RSSCT)	3.39 mg/g (PD)	0.42 mg/g (CD)	0.69 mg/g (PD)
As at 10 ppb (Freundlich)	5.0 mg/g	3.6 mg/g	1.2 mg/g

BV = bed volumes, PD = proportional diffusivity, CD = constant diffusivity

 $\underline{\mathbf{As}}$ = capacity calculated from loading or batch test



Efforts to Expand Range of Test Conditions





- Isotherm Model for Media Replacement
 - Gary Amy at CSU (AwwaRF, 2004; WERC, 2006)
- RSSCT model for Bed Volumes to BT
 - A. Aragon at SNL (SNL-AWTP, 2006)
- Klinkenberg model for Bed Volumes to BT
 - S. Deng, NMSU (SNL-AWTP, 2007)
- Vendors' models
 - Based on multiple installation and different water chemistries
 - May be proprietary



Isotherm prediction (Amy et al. 2004)

- Multivariate analysis based on parametric chemical studies with selected media over range of water chemistries.
- Freundlich Isotherm for E33

$$Q = K_F x [As]^{1/n}$$

$$K_F = 0.813 - 0.16442 \text{ x (pH-6.0)} - 0.001544 \text{ x (PO}_4) - 0.01936 \text{ x (SiO}_2) - 0.015267 \text{ x (V)}$$

$$1/n = 0.1066 + 0.090358 \text{ x (pH-6.0)} - 0.0000654 \text{ x (PO4)} + 0.018384 \text{ x (SiO2)} + 0.001825 \text{ x (V)}$$
• $R^2 = 52\%$; adjust for pH (7.5 to 8.5) and PO_4 (100 – 250 ppb)


Available from AwwaRF and WERC



Isotherm Model for Media Replacement

Calculate K_f and 1/n as function of pH, V, PO₄, SiO₂

Apply Freundlich Isotherm to calculate As adsorption capacity (µg As/mg-media)



Calculate media run length (days) per vessel Calculate number media replacements per year

= As capacity x Media mass $[As_{(in)} - As_{(eff)}]$ x ave. flow

Mass spent media /yr = number replacements x media mass/vessel

Obtain cost of media/yr




Parametric RSSCT studies with E33: Rapid tests of effects of water chemistry

100 //	
100 ug/L	20 ug/L
60 ug/L	0
60 mg/L	0
9.0	5.0
5 min	3 min
	60 mg/L 9.0

^{*} Nominal Nationwide groundwater concentration ranges for these constituents are taken from the USGS NAWQA Data Warehouse for Groundwater




E33 Arsenic Breakthrough Comparisons



Difference in performance of at least 3x (up to 18x)

E33 consistently performs much better at pH 5 (vs. pH 9) regardless of other water chemistry parameters



$$BV = 116797 - 9433 \ pH - 127 \ Si - 232 \ V - 238 \ As$$

$$R^2 = 87\% \qquad (no \ PO_4 \ dependence)$$



Klinkenberg Model (1948)

- Models ratio of adsorbent loading to the equilibrium adsorption amount at a given location and time.
- Can be programmed in Excel


$$\frac{c}{c_{\rm F}} \approx \frac{1}{2} \left[1 + \operatorname{erf} \left(\sqrt{\tau} - \sqrt{\xi} + \frac{1}{8\sqrt{\tau}} + \frac{1}{8\sqrt{\xi}} \right) \right]$$

- Assumptions
- (1) Isothermal conditions;
- (2) No axial dispersion;
- (3) Linear driving force for mass transfer
- (4) Linear adsorption equilibrium, i.e. constant K_d

function of influent c_F , porosity, position, velocity, sorption, mass transfer kinetics



Klinkenberg Model for E33 (Socorro Phase I)



Comparison between Breakthrough Curves Obtained in Socorro Pilot Test SC-10 with Predictions from Klinkenberg Model.



Outline of Talk

- Background why we have a new As MCL.
- Arsenic Water Technology Partnership
 - Screening of technologies for pilot studies
 - Sandia Labs Pilot Test program
- Frontiers of Science
 - Understanding media performance
 - Rapid testing techniques
- What this all means in the real world
 - Helping communities deal with the new Standard
 - Sandia arsenic website
 - NM Small Business Assistance program



Helping Communities

- Information gathered at Vendors Forum and Pilots available on Sandia Pilot project website:
 - http://www.sandia.gov/water/arsenic.htm
- WERC developed Comprehensive Arsenic Tool (CoAsT)
 - available at:

http://wercstation.nmsu.edu:8080/arsenic/AsTree.dsb

Summaries of BATs

- Several cost models
- Decision tree
- Beta-version of rate structure tool
- Sandia Rural Outreach Program
 - Summary report for communities in New Mexico
- NM Small Business Assistance Program





Arsenic Water Technology Partnership Pilot Demonstration Project



Pilot Demo Project Home

> Technology Evaluation

<u>Pilot</u> Demonstrations

Outreach

Publications

Partners 4 8 1

Contacts

The Arsenic Water Technology Partnership is supported with a \$13 million Congressional appropriation through the U.S. Department of Energy. The program is a multi-year effort designed to move innovative technologies from the bench-scale to pilot scale demonstration. This program will enable water utilities, particularly those serving small, rural communities and Indian tribes, to implement the most cost-effective solutions to their arsenic treatment needs. This goal is being met by carrying out three activities:

- conducting research to develop innovative, arsenic removal technologies with a focus on reducing energy costs, minimizing operating costs, and minimizing quantities of waste;
- demonstrating the applicability of innovative technologies to a range of water chemistries, geographic locales, and system sizes; and
- evaluating the cost effectiveness of these technologies and providing education, training, and technology transfer assistance to user communities.

The Awwa Research Foundation (AwwaRF) has managed the bench-scale research programs. WERC (A Consortium for Environmental Education and Technology Development) is evaluating the economic feasibility of the technologies investigated and conducting community education/technology transfer activities. Sandia National Laboratories (SNL) manages the pilot-scale demonstration program. During the period 2004-2006, Sandia National Laboratories has conducted pilot treatment demonstrations at six sites. Pilot communities and technologies were matched to examine a wide range of alternative technologies and site conditions. The classes of technologies tested include 1) Continuous Flow Systems (ion exchange, metal oxyhydroxides sorbents), 2) Batch Systems (Coagulation/Microfiltration), and 3) Reverse Osmosis. This website serves as a gateway to the activities supported by Sandia National Laboratories as part of the Arsenic Water Technology Partnership. Links are provided to:

- Evaluation of innovative commercial arsenic treatment technologies
- Educational <u>Short Courses</u> and <u>Vendors Forums</u> held as part of the New Mexico Environmental Health Conferences in 2003 - 2005.
- Results of Pilot Demonstrations
- Project publications
- Activities of other members of the Arsenic Water Technology Partnership



Arsenic Water Technology Partnership Pilot Demonstration Project



Pilot Demonstrations

t Demo Project <u>Home</u>

Evaluation

Pilot

monstrations

Socorro Anthony

Rio Rancho emez Pueblo

Pine Hill

Weatherford

<u>Outreach</u>

<u>Publications</u>

<u>Partners</u>

Contacts

Overview of Pilot Demonstrations

Siegel, M.D., Dwyer, B., Aragon, A. and Everett, R. 2005. <u>Pilot Demonstrations of Arsenic Treatment Technologies in the U.S. Department of Energy, Arsenic Water Technology Partnership Program [pdf 800kb]</u>

SAND2005-1909C, Sandia National Laboratories, Albuquerque, NM.

Malynda Aragon, 2006. <u>Pilot Demonstrations of Arsenic Removal Technologies - Sandia</u> <u>National Laboratories</u> [pdf 612kb]

SAND2006-7639P, Sandia National Laboratories, Albuquerque, NM.

<u>Sandia National Laboratories Arsenic Treatment Technology Demonstration Program</u>
[pdf 1.4mb]

Presented at the American Water Works Association Inorganics Contaminants Conference, January 31, 2006.

<u>Pilot Tests of Adsorptive Media Arsenic Treatment Technologies in the Arsenic Water</u> <u>Technology Partnership</u> 2006-0372C [pdf 811kb]

Presented at the National Groundwater Association Meeting on Naturally Occurring Contaminants, Albuquerque, NM, February 6, 2006.

Pilot Test Sites News Releases

- · Socorro, New Mexico
- · Anthony (Desert Sands), New Mexico
- Rio Rancho, New Mexico
- Jemez Pueblo, New Mexico
- Pine Hill, Ramah Navajo Reservation (New Mexico)
- · Weatherford, Oklahoma

Program Contact:

Malcolm Siegel, Sandia National Laboratories

Phone: 505-844-5426, FAX: 505-844-7354 or Email: msiegel@sandia.gov

Awwa Pessaarch



Sandia Water Initiative





Arsenic Water Technology Partnership Pilot Demonstration Project



Technology Evaluation

t Demo Projec Ho<u>me</u>

Technology Evaluation

Pilot monstrations

<u>Outreach</u>

<u>Publications</u>

<u>Partners</u>

Contacts

Introduction

The decrease of the drinking water standard (MCL) for arsenic from 50 µ/L to 10 µ/L in January 2006 could lead to significant increases in the cost of water for many rural systems throughout the United States. The Arsenic Water Technology Partnership (AWTP), a collaborative effort of Sandia National Laboratories, the Awwa Research Foundation (AwwaRF) and WERC: A Consortium for Environmental Education and Technology Development was formed to address this problem by developing and testing novel treatment technologies that could potentially reduce the costs of arsenic treatment. Each of the Partners develops or evaluates new technologies in their respective programs: AwwaRF manages a bench-scale research program through a series of competitive grants; WERC hosts an annual contest in which university students compete to provide the best solution to a design challenge involving arsenic treatment; Sandia National Labs has sponsored educational Short Courses on arsenic removal technology and evaluated cutting-edge commercial products in three annual Vendors Forums held during the annual New Mexico Environmental Health Conferences (NMEHC) in 2003, 2004 and 2005. The most promising of the technologies from these three programs are pilot tested at several field sites in collaboration with local water utilities.

This website describes the efforts of Sandia National Laboratories to evaluate commercial technologies for the pilot test program from 2003 to 2006. The educational <u>Short Courses</u> held at the NMEHC included invited talks on aspects of arsenic occurrence, health effects and treatment technologies. The <u>Vendors Forums</u> were designed to allow vendors of commercial technologies to present product descriptions to the conference participants and to allow objective evaluation by technical experts. During a closed session, the technologies were reviewed by teams of recognized experts in water treatment and related fields and were assigned numerical scores based on expected performance and costs. <u>Table 1</u> lists all the companies that participated in the Forums, identifies their products and provides electronic links to points of contacts or company websites. Table 2 describes the rankings of technologies for each of the 3 Vendors Forums and identifies those being pilot tested at the field scale by Sandia National Laboratories.

Other technologies were evaluated through other methods such as by independent review of product performance and cost by Sandia staff, technical review by the Technical Advisory Committee and the Partnership Management Committee of the AWTP. Several of these technologies were chosen for pilot scale demonstrations; Table 3 provides descriptions of these products. A list of the technologies being tested at each of the 5 pilot sites is given in Table 4.

Table 1. Vendor Forum Participants

Table 1. Vendor Forum Participants

Table 2. Vendor Rankings for each Forum

Table 3. Vendors Not Participating in Forum but Currently or Potentially Involved in Pilot Studies

Table 4. Vendor Participation in Pilot Tests

All of the technologies that were reviewed are described in this website. Treatment methods are categorized as adsorptive media, coagulation/filtration/membranes or other technologies. An alphabetical index to all technologies is also provided. Other information about the technologies and related topics can be found in two summary reports and the websites for each of the Short Courses and Vendors Forums, which include links to the presentations given at these events.

Treatment Methods

Category Listing

Adsorptive media
Coagulation/Filtration/Membranes
Other Technologies

Alphabetical Index

Summary Reports

- <u>Development and Evaluation of Innovative Arsenic Adsorption Technologies for Drinking Water by the Arsenic Water Technology Partnership</u>, SAND2006-0113C [pdf 248kb], National Groundwater Association Meeting on Naturally Occurring Contaminants, Albuquerque, NM, February 6, 2006
- Malcolm Siegel, Paul McConnell, Randy Everett, Carolyn Kirby 2006. <u>Arsenic Treatment Technology Vendors Forums Summary Report</u> [pdf 220kb]
 SAND2006-5423, Sandia National Laboratories, Albuquerque, NM.

Event Websites

- Arsenic Treatment Technology Short Courses
- Arsenic Treatment Technology Vendors Forums

Program Contact:

Malcolm Siegel, Sandia National Laboratories

Phone: 505-844-5426, FAX: 505-844-7354 or Email: msiegel@sandia.gov

Awwa Research Foundation



Sandia Water Initiative





Arsenic Water Technology Partnership Pilot Demonstration Project Outreach



: Demo Projec Home

<u>Fechnology</u> Evaluation

<u>Pilot</u> monstrations

Outreach

ublications

<u>Partners</u>

<u>Contacts</u>

James L. Krumhansl, Kathleen C. Holt, Heather Himmelberger, Susan Butler, Matt Ziegler, and Bruce Thomson, 2007. <u>Summary of Resources Available to Small Water</u> <u>Systems for Meeting the 10 ppb Arsenic Drinking Water Limit</u> [pdf 1mb] SAND2006-6943, Sandia National Laboratories, Albuquerque, NM.

Sandia Corporation | Site Contact | Site Map | Privacy and Security

NM Small Business Assistance Program

Objective

- Assist small NM businesses in water treatment problems to grow their business
- Qualified businesses
 - Satisfy definition of 'small business'
 - NM tax ID
 - <500 employees and/or cap on annual revenues</p>
- Free technical Assistance
 - Urban \$10,000/yr
 - Rural \$20,000/yr
- Applications still being accepted for 2008



Possible Assistance by Sandia

Sandia National Labs can:

- Provide training on tools and data obtained in AWTP
- Provide initial analysis of options for arsenic treatment.
- Screen potential treatment vendors.
- Coordinate pilot tests by vendors.
- Provide rapid turn-around time for water analyses (not EPA certified) to aid design and tests.
- Review proposals from companies for water treatment systems.
- Sandia cannot compete with private businesses.



Current and Future Projects













Paakweree Water Cooperative

New Mexico Utilities

Pine Hill School



Summary - Research Program - Applications



Use rapid testing methods and models to to narrow down choices for the most effective adsorptive treatment technology for small systems.






RSSCT & isotherm Days-weeks

Full scale treatment 12-24 months

Pilot scale 6-12 months



Models: days- hrs



Take Home Message

- 1. Don't panic! the water won't kill you right away.
- 2. Don't make hasty decisions about water treatment system for arsenic removal.
- 3. The right system for your community depends on:
 - Available (non-treatment) options
 - Financing options
 - Operator training
 - Existing infrastructure
 - Water chemistry
- 4. There's no magic bullet!



For More Information and Assistance:

Arsenic Partnership Website

http://www.arsenicpartners.org/

Sandia Website

http://www.sandia.gov/water/arsenic

→ Papers, Presentations, Vendor Information, Pilot Results

WERC CoAsT Website

http://www.werc.net

→ Click on Outreach tab, then CoAsT



Thank you for your attention

Questions?

msiegel@sandia.gov


505-844-5426







Arsenic Sources and Occurrences





Things we looked for in pilot sites


- As concentration (>10 ppb)
- Example ground water composition that will help other communities
 - pH, TDS, foulants such as Fe, Mn, silica, and organics
 - As(III)/As(V)
 - Competing ions (V, SO₄, etc.)
 - Other contaminants of concern/benefit (e.g, Ra, U, ClO₄, F)
- Small size of system to be treated (< 10,000 users)
- Community support facilitates rapid deployment
 - Water utility
 - Municipal government
- Ability to deal with residuals/treated effluent
- Rural and Native American communities that would benefit from assistance



Chemical Compositions of Media

Media	Constituents (XRD)	Dominant Elements (EDS)
Isolux 302M	Amorphous zirconium oxide/hydroxide	Zr, O
Metsorb	Crystalline TiO ₂ (Anatase)	Ti, O
ARM200	Amorphous Iron oxide/hydroxide (or very poorly crystalline <i>Hematite</i>)	Fe, O
ArsenX ^{np}	Amorphous iron oxide/hydroxide Resin impregnatation	Fe, O, C
E33	Iron oxide/hydroxide (Goethite)	Fe, O


pH and Sorption by adsorptive media Example: Fe(OH)₃





Socorro Pilot Phase I and Ila Events

S4 = **ARM200** (**FeOx**); **S5** = **AsXnp** (**resin**); **S6** = **Metsorb** (**TiOx**); **S9** = **E33** (**FeOx**)




Not a linear scale!



Media Performance Socorro, NM

S4 = ARM200 (FeOx); S5 = AsXnp (resin); S6 = Metsorb (TiOx); S7 = Isolux (ZrOx); S9 = E33 (FeOx)

Socorro Arsenic Removal



^{*}AsXnp batch was defective, ARM200 was pre-production batch



Research Program - Components

- Materials characterization
 - Pre-test and post studies, temperature-ageing studies
 - XRD, Surface area (BET), pore size distribution
 - Particle morphology and surface chemistry
 - Attrition loss
 - Post-mortem pore fluids and solids
- Batch sorption studies
 - Kinetic (15°C and 40°C)
 - Isotherms (linear, Freundlich, Langmuir)
- Rapid small scale column tests (RSSCTS)
- Develop simple model that could predict media performance from Lab tests

